

Wonderfloor is the flagship brand of RMG Polyvinyl India Limited. Wonderfloor offers flooring solutions for a wide range of commercial and residential applications. The range has a flooring for every usage, for every application. Starting from healthcare flooring to sports flooring, restaurant flooring to supermarket flooring, transport flooring to dance flooring, the brand Wonderfloor meets all the varied requirements of a modern day living and work spaces: homes, offices, factories, sports complexes, metro trains, hospitals, hotels, porta cabins etc.



6

Not only in India, but across the world, Wonderfloor is a preferred flooring brand: In Americas, Europe, Middle East as we aim to further widen our global footprints.





Amber

**Dimensions:** Thickness: 1 mm, 1.5 mm, 2 mm, 3 mm | Roll Width: 1.50 mtr, 2 mtr  
Roll Length: 15, 20 linear mtr | Tile Size: 305 mm x 305 mm



# ROBUST | Heavy-duty Flooring

Robust is heavy duty, high quality, resilient, flexible and highly durable marbled PVC Flooring. It is designed to withstand high traffic and abrasion. This product has a unique marbling pattern that adds to the aesthetics of the area where they are installed as it is produced having one base colour and two contrast colours used for marbling by a special hot granulation process which is unique in nature.

## SALIENT FEATURES

- They are 'P' rated and have a slip resistance of R9
- Available in rolls or tiles
- The flooring is embossed with "Raindrop" embossing design which enables quick cleaning & easy maintenance.
- PUR surface protection
- Can be thermo welded for joint free installation
- Application areas : Offices, Shops, Factories, Porta Cabins, Auditoriums, schools, libraries, healthcare etc.



Oyster



Carolina Blue



Ice Land



Emerald Green



Saffrony



Iceberg



Florida



Lee Cooper



Coral Feast



AMBER



Desert Sand



Blue water



Mercury

**SALIENT FEATURES**

- They are "P" rated and have a slip resistance of R9
- Available in rolls or tiles
- The floorings are embossed with "Raindrop" embossing design which enables quick cleaning & easy maintenance.
- Robust Ultima (2.0 mm) is available with PUR (Polyurethane) surface protection providing resistance against scratches & dirt accumulation and also ensures quick cleaning/ mopping
- Can be thermo welded for joint free installation
- Application areas : Offices, Shops, Factories, Porta Cabins, Auditoriums, schools, libraries, healthcare etc.

**DIMENSIONS AVAILABLE**

Thickness	1 mm, 1.5 mm, 2 mm, 3 mm
Roll width	1.50 mtr, 2 mtr
Roll length	15 linear mtr, 20 linear mtr
Tile size	305 mm x 305 mm

**PERFORMANCE CHARACTERISTICS**

CHARACTERISTICS	SYMBOLS	TEST METHOD	RESULTS
TOTAL WEIGHT		EN 430	3,40 KG /SQ. FOR 2.00 MM
DIMENSIONAL STABILITY		EN 434	≤0,40%
RESIDUAL INDENTATION AFTER STATIC LOAD		EN 433	≤0,10MM
FLEXIBILITY		EN 435	40 MM MANDREL, PASSED
ABRASION RESISTANCE		EN 660-2 EN 649	WEAR GROUP P
SURFACE SPREAD OF FLAME		BS 476 PART 7	CLASS 1
FIRE PROPAGATION		BS 476 PART 6	(I)=10,8 CLASS "O" (II)=1,7
HYGIENE			TEST RESULT DEMONSTRATES THAT IT INHIBITS GROWTH OF MICROBES
COLOUR FASTNESS TO DAY LIGHT		ISO 105-BO2	>BLUE WOOL STANDARD 5
SLIP RESISTANCE		DIN 51130	R 9
BEARING A CASTOR CHAIR		EN 425	SUITABLE/CONTINUOUS USE
RESISTANCE TO CHEMICALS		EN 423	NO VISIBLE CHANGE
SOUND ABSORPTION		ISO 140-8 EN ISO 717-2	Δ LW = 5db
PERFORMANCE CLASSIFICATION		EN 685	34, 41